




Publication No. II 3477-A
10/97

INSTALLATION INSTRUCTIONS

for the

KODAK Miniloader 2000 VAN-KIT

CAT. Number 7186380



CAUTION

The ML2000 weighs 250 KGs (551lbs) without the possible accompanying M35 film processor.

The equipment must be adequately secured to the vehicle.

The customer and / or coachbuilder to be notified of the fixing requirements;

To secure this weight in the vehicle ensure the floor is capable of supporting the equipment.

Adequate fixings are used, e.g. screws, washers & nuts which are rust proof etc.

Ensure that no component of the vehicle is damaged by the install e.g. brake pipes, electrical cables.

Positioning the Autoloader over the "Mounting Anvil" of the articulated trailer is a potential hazard from a fixing criteria this will require special install arrangements "if " at all possible. The coachbuilder's are the only people who can perform this task.

PLEASE NOTE

The information contained herein is based on the experience and knowledge relating to the subject matter gained by Kodak prior to publication. No patent license is granted by this information. Kodak reserves the right to change this information without notice, and makes no warranty, express or implied, with respect to this information. Kodak shall not be liable for any loss or damage, including consequential or special damages, resulting from the use of this information, even if loss or damage is caused by Kodak's negligence or other fault.

TABLE OF CONTENTS

INTRODUCTION	1-2
SPACE REQUIREMENTS.....	1-2
PACKING LIST	1-3
INSTALLATION	1-4
OPERATING MODE.....	1-11
TRANSPORT SAFETY PRECAUTIONS	1-12

INTRODUCTION

The VAN-KIT is used to install a KODAK Miniloader 2000 in a VAN. As a standard VAN does not exist, the adaptation of the BASE PLATE and REAR WALL PLATE to the VAN has to be made during installation. The necessary mounting hardware (screws, anchors etc.) must be provided locally. They are not part of the VAN-KIT.

The Kit consists of a SHOCK ABSORBER SANDWICH and the REAR WALL SHOCK ABSORBER ASSEMBLY.

To get access for service a QUICK DISCONNECT has to be released and 2 SHOCK ABSORBERS at the rear must be removed. The ML2000 can then be moved forward.

SPACE REQUIREMENTS




figure 1-1

The lateral space of 20cm (8 inch) is needed, because the ML2000 swings during a bus ride (especially on a bumpy road). The lateral space of 50 cm(20 inch) is required for the service personal to take out the rear SHOCK ABSORBERS in case service is necessary.

The 50 cm space should be preferably on the left side.

PACKING LIST

INSTALLATION INSTRUCTIONS	II 3477-A	1
WALL MOUNTING PLATE	9301401	1
BASE PLATE	9301501	1
REAR MOUNTING PLATE	9301411	1
FRONT MOUNTING PLATE	9301421	1
SHOCK ABSORBER SANDWICH	9309163	1
REAR MOUNTING BRACKET left	9309041	1
REAR MOUNTING BRACKET right	9309061	1
REAR SHOCK ABSORBER	9301621	2
LOCKING PLATE	9301461	1
TRANSPORT LABEL	9301561	1
SCREW M6x10 ***	4284044	9
SCREW M6x20 ***	4280440	4
WASHER 6.4 mm	4480121	9
VELCRO top / bottom	5001718 / 5001721	1

***** NOTE**

No NUTS are required for these SCREWS. All parts are provided with the required threads.

INSTALLATION

1. Mount the MOUNTING PLATE of the REAR WALL SHOCK ABSORBER ASSY to the wall. If necessary drill additional holes into the PLATE.

NOTE

The necessary mounting hardware is not provided by KODAK




figure 1-2

2. Mount the REAR MOUNTING PLATE to the ML2000. Use 2 SCREWS M6x20 with WASHERS.




figure 1-3

NOTE

Before fastening the SCREWS set the MOUNTING PLATE to the correct height. Use the BASE PLATE as a GAUGE.

- 3.** Open the FRONT DOOR of the ML2000 STAND. Mount the FRONT MOUNTING PLATE (this is the PLATE with the QUICK DISCONNECT). Use 2 SCREWS M6x20 with WASHERS.

NOTE

Before fastening the SCREWS set the MOUNTING PLATE to the correct height. Use the BASE PLATE as a GAUGE.




figure 1-4

- 4.** Take out the MOUNTING SCREW of the PNEUMATIC ASSEMBLY and retain it.




figure 1-5

5. Take off the REAR PANEL of the ML2000 STAND.
6. Insert the SHOCK ABSORBER SANDWICH. First tighten the 4 COUNTERSUNK SCREWS. This makes the SANDWICH flat enough to become inserted.

NOTE

The v-shaped cut-out must be down and pointing to the rear of the ML2000. It must be engaged with the LOCATING PIN of the ML2000 STAND.




figure 1-6

7. Fix the SANDWICH to the ML2000 with 5 SCREWS M6x10 and WASHERS. Do not tighten the SCREWS.




figure 1-7

- 8.** Take out the 4 COUNTER SUNK SCREWS of the SANDWICH.




figure 1-8

- 9.** Tighten the SCREWS inserted in step 7.
- 10.** Take out the 4 SCREWS of the SPACER BRACKETS left and right and take out the SPACER BRACKETS. They are no longer needed.




figure 1-9

11. Fasten the PNEUMATIC ASSEMBLY. Use the SCREW removed in step 4.
12. Mount the REAR PANEL to the ML2000 STAND.
13. Take out the 4 DUMMY PLUGS at the rear of the ML2000.




figure 1-10

14. Mount the 2 REAR MOUNTING BRACKETS to the ML2000. Use SCREWS M6x10. Do not use longer SCREWS. The GEAR BOX of the FILM POCKET STEPPER MOTOR might become damaged.




figure 1-11

15. Mount the BASE PLATE to the floor.

Note

Necessary mounting hardware is not provided by Kodak.




figure 1-12

16. Roll back the ML2000 until the REAR- and FRONT MOUNTING BRACKETS are fully engaged with the BOLTS of the BASE PLATE mounted to the floor.

17. Close the QUICK DISCONNECT.

- 18.** Insert both REAR SHOCK ABSORBERS. They slide into their GUIDES.




figure 1-13

- 19.** Place the self adhesive LABEL with TRANSPORT HINTS onto the ELECTRONIC BOX.





figure 1-14

- 20.** Mount the VELCRO to the ML2000 SIDE PANEL and to the FRONT DOOR.



format 1-15

OPERATING MODE

During operation the LOCKING PLATE must be installed at the REAR SHOCK ABSORBERS. This LOCKING PLATE prevents the ML2000 from swinging during normal operation.

Note

Instruct the OPERATOR to carry out this measure.




figure 1-16

TRANSPORT SAFETY PRECAUTIONS

During transport the following safety precautions must be taken to prevent damages to the ML2000.

NOTE

Instruct the OPERATOR to follow these SAFETY PRECAUTIONS.

1. Take out all SUPPLY MAGAZINES, the RECEIVING MAGAZINE and store them in a safe place.




figure 1-17

2. Close the FRONT DOOR and secure it with the VELCRO.
3. Remove the LOCKING PLATE and store it in a safe place.
4. Ensure that the QUICK DISCONNECT is closed.
5. Switch off the ML2000.

Kodak AG
Hedelfinger Str. 54-60
70327 Stuttgart
Germany

Printed in Germany



CUSTOMER EQUIPMENT SERVICES KODAK AG STUTTGART