

## **MODIFICATION INSTRUCTIONS**

for the

**KODAK MULTILOADER 700**

**Service Code 3053**

**MODIFICATION No. 4**

**Type 1**

**PURPOSE:**

**to prevent film jams in the CONVEYOR.**

IMPORTANT: Use qualified personnel to install this MODIFICATION

SERVICE EFFECTS: DEFLECTOR is added.

SPECIAL REQUIREMENTS: None

Serial NUMBER: All units with serial numbers below 1079 may be affected.

INSTALLATION TIME: approx. 1 hour

SPECIAL TOOLS: none

PARTS STATUS: Parts are available from Parts Services KODAK AG

PARTS REQUIRED: DEFLECTOR Part No. 9191661

**PLEASE NOTE**

The information contained herein is based on the experience and knowledge relating to the subject matter gained by Kodak prior to publication.

No patent license is granted by this information.

Kodak reserves the right to change this information without notice, and makes no warranty, express or implied, with respect to this information. Kodak shall not be liable for any loss or damage, including consequential or special damages, resulting from the use of this information, even if loss or damage is caused by Kodak's negligence or other fault.

## **INSTALLATION**

- 1** Open COVER RIGHT and COVER TOP.
- 2** Remove the WIRE TIE on MOTOR M5.




figure 1

- 3** Unplug MOTOR M5
- 4** Remove the MOUNTING SCREWS of MOTOR M5. See figure 1.
- 5** Remove the TIMING BELTS. See figure 1.

**6** Remove MOTOR M5.




figure 2

**7** Remove the SCREW. See figure 2.

**8** Place the SCREW and the WASHER for the MOUNTING BOLT in to the hole of the DEFLECTOR 9191661.

- 9** Place the DEFLECTOR 9191661 under the SLIDING PLATE. See figure 2.
- 10** Fasten the SCREW on the MOUNTING BOLT. Check that the rear edge of the DEFLECTOR touches against the SLIDING PLATE. See figure 2.
- 11** Reinstall the MOTOR M5. See figure 1. Do not tighten the SCREWS.
- 12** Reinstall the TIMING BELTS. Adjust the tension of the TIMING BELTS by positioning MOTOR M5. Tighten the SCREWS on the MOUNTING PLATE of MOTOR M5.
- 13** Plug in CONNECTOR of MOTOR M5.
- 14** Install new WIRE TIE on MOTOR M5.
- 15** Close TOP COVER.
- 16** Close COVER RIGHT.
- 17** Circle No. 4 on the MODIFICATION LABEL. See figure 3.




figure 3



**CUSTOMER EQUIPMENT SERVICES KODAK AG STUTTGART GERMANY**