

MODIFICATION INSTRUCTIONS

for the

KODAK MULTILOADER 700

Service Code 3053

Modification No. 13

Type 2

Purpose:

To prevent FILM JAMS at the ENTRANCE of the CONVEYOR by holding the movable DEFLECTORS at the ENTRANCE of the CONVEYOR in the correct position after the EXIT DOOR is opened.

SERIAL NUMBERS:	Up to SN 1468 (50Hz units)
	Up to SN 5223 (60Hz units)
INSTALLATION TIME:	Approx. 1 hour
SPECIAL TOOLS:	none
PARTS REQUIREMENT:	2 x SPRING Part No. 9192986

PLEASE NOTE

The information contained herein is based on the experience and knowledge relating to the subject matter gained by Kodak prior to publication.

No patent license is granted by this information.

Kodak reserves the right to change this information without notice, and makes no warranty, express or implied, with respect to this information. Kodak shall not be liable for any loss or damage, including consequential or special damages, resulting from the use of this information, even if loss or damage is caused by Kodak's negligence or other fault.

- 1.** Open right COVER.
- 2.** Disconnect ML 700 from TUNNEL.
- 3.** Remove REAR COVER.
- 4.** Remove SCREW with WASHER. See figure 1.





figure 1



- 5.** Install SPRING 9192986 with SCREW and WASHER between FRAME of ML700 and MOUNTING SHAFT of SLIDING PLATE. See figure 2.

Note:

Do not bend the SPRINGS. Check that the SLIDING PLATE rests tightly on the SUPPORT SHAFT after tightening the SCREW.

- 6.** Install SPRING 9192986 to the LEFT MOUNTING SHAFT OF SLIDING PLATE as described in STEP 4 and 5.

7. Circle No. 13 on Mod Label.




figure 3

8. Install REAR COVER.

9. Connect ML 700 to the TUNNEL.

10. Close all COVERS.

11. Run TEST CYCLES.



CUSTOMER EQUIPMENT SERVICES KODAK AG STUTTGART GERMANY