

MODIFICATION INSTRUCTIONS

for the

***KODAK X-Omatic* MULTILOADER 300**

Service Code 3058

MODIFICATION No. 30

Type 1 REQUIRED

PURPOSE:

To install new software and to improve the reliability.

IMPORTANT : Use qualified service personnel to install this modification !

SERIAL NUMBERS : 1001-1445

INSTALLATION TIME : Approx. 2.5 hours

SPECIAL TOOLS : IC EXTRACTOR TL4430
TORX KEYS TL 3261

PARTS REQUIREMENTS : MOD KIT #30 PN 9221000

PLEASE NOTE

The information contained herein is based on the experience and knowledge relating to the subject matter gained by Kodak prior to publication.

No patent license is granted by this information.

Kodak reserves the right to change this information without notice, and makes no warranty, express or implied, with respect to this information. Kodak shall not be liable for any loss or damage, including consequential or special damages, resulting from the use of this information, even if loss or damage is caused by Kodak's negligence or other fault.

PARTS LIST

<u>PART NO.</u>	<u>DESCRIPTION</u>	<u>QUANTITY</u>
-----------------	--------------------	-----------------

9225790..... MOD KIT 32

The KIT contains:

4281551.....	SCREW M3x16.....	1
4281631.....	SCREW M5x25.....	1
4853236.....	NUT M4.....	1
4853256.....	LOCK NUT M4 with blue insert	3
9215302.....	CONNECTING ROD.....	1
9215803.....	CLUTCH DISK 1	1
9215793.....	CLUTCH DISK 2	1
9219901.....	RING.....	1
9225780.....	CLUTCH SPRING	1
9219841.....	SPRING HOOK 1	1
9219851.....	SPRING HOOK 2	1
9219831.....	REJECTER SPRING	1